

# STROBE-BRIK™

## SB-010QD 7W LED Strobe Architectural-use DMX-controlled LED strobe

### **World's First and Only!**

Use the LED Strobe-Brik system to add sparkle to your iconic architecture. Based on the very successful xenon Strobe-Brik system, the LED system provides individual DMX control of hundreds of small LED strobes. The SB-010QD 7W strobe uses high quality Luxeon Rebels, providing some of the highest efficacies available in any LED.



### **Applications**

- Icon architecture
- Themed spaces
- Casinos
- Dark ride and show effects

### **Features**

- Mount anywhere, small-profile strobe.
- Strobes are individually DMX-addressed for complete control.
- Exterior-rated strobe housing
- Threaded-base strobe fixture for easy, no-tools installation.
- Integrate with any number of related effects.
- Many mounting options available.

### **Available colors:**

- SB-010QD-RED, Red
- SB-010QD-GRN, Green
- SB-010QD-BLU, Royal Blue
- SB-010QD-CYA, Cyan
- SB-010QD-RED-AMB, Red-Orange
- SB-010QD-AMB, Amber
- SB-010QD-CWH, Cool White
- SB-010QD-NWH, Neutral White
- SB-010QD-WWH, Warm White

### **Specifications**

- 7W or greater @700mA each
- 0.80" dia. X 1.66" long
- For use with 7W LED Strobe-Brik controllers
- One DMX channel per strobe
- 50,000 hrs life at 700mA with 70% lumen maintenance.

SB-010QD shown with  
L-bracket, connector, and cable



# STROBE-BRIK™

## SB-010QD 7W LED Strobe Architectural-use DMX-controlled LED strobe

### 7W LED strobe data

Part Number	Type	Watts @700mA	Luminous Flux [Lm] each strobe @ 700 mA	Dominant Wavelength [nm] @ 350 mA	Viewing Angle [Degrees]
SB-010QD-RED	RED	7.14	255	620-645	140
SB-010QD-GRN	GREEN	7.56	435	520-550	140
SB-010QD-BLU	ROYAL BLUE	7.56	1575 mW	440-460	140
SB-010QD-CYA	CYAN	7.56	390	490-520	140
SB-010QD-RED-AMB	RED-ORANGE	7.14	300	613-620	140
SB-010QD-AMB	AMBER	7.14	195	584-597	140
SB-010QD-CWH	COOL WHITE	7.56	435	4500-10000 K	140
SB-010QD-NWH	NEUTRAL WHITE	7.56	435	3500-4500 K	140
SB-010QD-WWH	WARM WHITE	7.56	330	2670-3500 K	140

