

SPECIFICATIONS

OUTPUT	Current Range	0 ~ 3.8 Amps
	Rate Power	45.6 Watts
	Low Ripple & Noise Voltage	2Vp-p
	Over Voltage Protection	13.8 ~ 16.0 Volts
	Short Circuit Protection	Hiccup mode, auto recovery
	OTP Protection	95°C ±10°C detect on heat sink of power transistor
	Start-up Time	<1500 ms @230 VAC or 3000ms @115 VAC, full load
INPUT	Voltage Range	90–295 VAC, 127–417 VDC
	Frequency Range	47–63 Hz
	Power Factor	>0.9 at 75-100% load, 115/230 VAC
	Efficiency	83.5% typical
	Input Current	Maximum 0.55 amps @ 115 VAC or 0.25 amps @ 230 VAC
	Inrush Current	40 amps typical @ 230 V
EMC	Conducted Emissions	EN55015
	Radiated Emissions	EN55015
SAFETY	Safety Standards	UL8750 for UL1310 Class 2 TUV EN61347-1 CAN/CSA C22.2 No. 223-M91 IP64

*Specifications subject to change

PACKAGING

24 individual power supply units per case.

www.LuxemBright.com

©2010 CAO Group, Inc. Data subject to change. Copyright reserved by CAO Group. No part of this datasheet may be reproduced in any form without the permission from the publisher. For product information and a complete list of sales representatives, please go to our website.

For technical assistance please call:
US/Canada: 1+ (877) 236-4401 or 1+ (801) 256-9282

BIRKET Specialty Lighting
A DIVISION OF BIRKET ENGINEERING, INC.

AUTHORIZED DISTRIBUTOR

www.birketspecialtylighting.com

(407) 290-2000



CAO GROUP, INC.
Easier · Faster · Better™

Solid State Lighting

ISO 9001 CERTIFIED
TS 16949 CERTIFIED FACTORY



3AL-DS0028A 1/10NOV2010